



**Ordering example:**  
PG 32 T12 22,5°

PG: Type  
32: Piston Ø  
T12: Sensing system  
22,5°: Opening angle

**Opte:**  
22,5°, 45° and 75° available

\* Tolerance for dowel holes ± 0.02, for threaded holes ± 0.1.

**Accessories:**  
Protection sheet

**Ordering example Tünkers sensing systems:**

...T00 Without sensing...T12  
...T12 Inductive sensor 24 V, 1 output with integrated LED's

**Option:**  
Clamping jaw (not included in the scope of delivery)

Type	Clamping force at 5 bar (Nm)	Working pressure with oil-free air (bar)	Maximal pressure with oil-free air (bar)	Connection (G)	Opening-and closing time (sec.)	Weight ~ (kg)	L1	L2	L3	L4 ±0,1	L5 ±0,1
PG 32	900	5	6	1/8	1	0,87	158	116	30,5	6	30
PG 40	1300	5	6	1/8	1	1,5	198	145	38	7,5	38

Type	L6 ±0,1	L7	L8 ±0,02	L9 ±0,05	L10	L11	L12	B1	B2	B3 ±0,1	B4 ±0,1	B5 ±0,1	B6	B7	B8	B9	B10	D1 Ø	D2 Ø	D3 Ø	D4 Ø
PG 32	17,5	20	19	2,5	55	45	11,5	24	36	28	20	30	23	16	3	28	18	M6	M5	8,5	M6
PG 40	24	25	24	3	56	55	15	30	46	35	25	38	29	20	3	36	31	M6	M6	11	M6