FURTHER FEATURES AND OPTIONS OF THE UP SERIES

W

THE PARALLEL-PLANE CLAMP

Patented compressed air saving principle of the U-series

Up to 30% reduced compressed air consumption due to force-optimised knee-lever mechanism and use of smaller drive cylinders.

Dual query concept for simple change with robust pin contacts



Both air connections located in optimal positions in the cylinder floor



Stepless setting of the opening angle from 0°-135°



Servoelectric parallel clamp IP 63

- 24V servo drive
- Play-free and self-limiting trapezoidal spindle
- Freely adjustable opening angle with the option of intermediate positions
- Conditioning monitoring
- Plate thickness detection
- Detection of faults
- Detection of faulty parts
- Wear control



H / HO / HD

The version with weld-resistant

surface coating

The version with additional locking in opened and/or closed position through integrated stop valves in the cylinder floor



RB

The version with a mechanical catch in the cylinder floor







TÜNKERS[®] Maschinenbau GmbH · Am Rosenkothen 4-12 · DE-40880 Ratingen Tel. +49 (0)2102 4517-0 · Fax +49 (0)2102 4517-9999 · info@tuenkers.de · www.tuenkers.de



The new clamp generation for parallel-plane clamping with constant clamping force





CORRECT CLAMPING WITH THE UP-SERIES – THE PARALLEL-PLANE CLAMP WITH CONSTANT CLAMPING FORCE



Special mechanical systems integrated in the housing with two movement steps Step 1: Pivoting

The clamping arm is pivoted/turned a maximum of 135° from open position to the clamping position

Step 2: Clamping

Parallel-plane clamping process in which the arm is move vertically up to 5 mm to the workpiece. In the parallel-plane clamping process, constant clamping force is available regardless of the arm length.

Parallel-plane clamping

Traditional clamp Pivoting clamping arm

UP clamp Parallel-plane increment clamping arm





Clamping arm pivots onto the component

Clamping arm always places parallel pressure on the component

Automatic mechanical balance

In the clamping/work range of 0-5 mm, plate thickness deviations can be balanced out to a certain extent by model variants, quality deviations, or contour piece wear. No danger of component deformation due to twisting, as the contour piece is placed in parallel.



Constant clamping force

Thanks to special mechanical translation systems, the clamping force of the UP-series is always constant and independent clamping arm length. The pressure regulator integrated in the cylinder can also steplessly set the clamping force for the application.

Traditional clamp



With traditional clamps the clamping force reduces as the distance from the fulcrum increases.

Clamping independently of the fulcrum

To avoid tensile or shearing forces on the turning section, with traditional clamps the clamping point must be placed in the fulcrum -> less flexibility when installing equipment.

Clamping via turning point, shearing effect













- No danger of shearing/tensile forces on the component. Clamp can therefore also be placed under the component level, saving space. Optimal access, e.g. with welding tongs

仓

MOVER