



Vario series – Pneumatic clamps for line production in the body assembly

- Stepless adjustable opening angle:  
5-135°
- No specification of opening angles necessary
- Easier accessibility of opening angle adjustment
- Smaller interfering contour with size 63
- More precise Target / more precise switch point by improved switch lug in size 50/63
- Established in fixture building since 2011



# Opening angle adjustable 5-135°

- Easy adjusting of opening by turning the piston rod from 5-135°
- The adjustable opening angle can be read on the engraved angle scale at the outside
- One locking screw



- Cylinder in oval profile with integrated cushioning in end position



- Main drive shaft supported by needle bearing



- Release Pin to unlock clamp without air



- Stepless adjustable opening angle 5-135°
- Integrated cushioning in end position
- Optimal drive shaft
  
- Advantages Vario Clamp V... BR2 towards BR1
  - Only one clamp!
  - Reduction of variants in stock
  - Optimized housing and interfering contour

## Thank you for your attention

TÜNKERS Maschinenbau GmbH  
Christian Eickhoff  
Am Rosenkothen 4-12  
40880 Ratingen

Telefon +49 (0) 2102-45 17-290  
Telefax +49 (0) 2102-45 17-9999

E-Mail [christian.eickhoff@tuenkers.de](mailto:christian.eickhoff@tuenkers.de)  
Internet [www.tuenkers.de](http://www.tuenkers.de)

